

## ➤ FLUID FORCE 4000 HOUR – THE SCREW WARRANTY LUBRICANT



|                             | Test Method        | Fluid Force 4000 Hour Screw Warranty Lubricant |
|-----------------------------|--------------------|------------------------------------------------|
| ISO Viscosity Grade         | ISO 3448           | 46                                             |
| Kinematic Viscosity         | ASTM D445          |                                                |
| at 40 °C                    | mm <sup>2</sup> /s | 46                                             |
| at 100 °C                   | mm <sup>2</sup> /s | 6.8                                            |
| Viscosity Index             |                    | 102                                            |
| Density at 15 °C            | kg/m <sup>3</sup>  | ASTM D1298                                     |
| Flash point COC             | °C                 | ASTM D92                                       |
| Pour Point                  | °C                 | ASTM D97                                       |
| Ash, sulphated              | %                  | DIN 51575                                      |
| Air release at 50 °C        | min                | ASTM D 3427                                    |
| Water separability at 54 °C | min                | ASTM D 1401                                    |
| FZG Test                    | load stage failure | CEC-L07-A-85                                   |
| Colour                      |                    | Blue                                           |

These characteristics are typical of current production.  
Whilst future production will conform to specification, variations may occur.

## ➤ FLUID FORCE FOOD GRADE – SCREW LUBRICANT

CompAir food grade lubricants is a hydro tested mineral oil for food and environmentally sensitive applications. Supported by the food grade flushing oil (Fluid Force Prime) they offer the following additional benefits:

- Non Toxic, odourless and tasteless
- 50% more biodegradable than standard mineral oil
- Meets all major environmental legislative requirements

Available in 20 & 209 Litre packs.

|                             | Test Method        | Fluid Force Food Grade Screw Lubricant |
|-----------------------------|--------------------|----------------------------------------|
| ISO Viscosity Grade         | ISO 3448           | 46                                     |
| Kinematic Viscosity         | ASTM D445          |                                        |
| at 40 °C                    | mm <sup>2</sup> /s | 46                                     |
| at 100 °C                   | mm <sup>2</sup> /s | 7.3                                    |
| Viscosity Index             |                    | 133                                    |
| Density at 15 °C            | kg/m <sup>3</sup>  | ASTM D1298                             |
| Flash point COC             | °C                 | ASTM D92                               |
| Pour Point                  | °C                 | ASTM D97                               |
| Ash, sulphated              | %                  | DIN 51575                              |
| Air release at 50 °C        | min                | ASTM D 3427                            |
| Water separability at 54 °C | min                | ASTM D 1401                            |
| FZG Test                    | load stage failure | CEC-L07-A-85                           |
| Colour                      |                    | Clear                                  |

These characteristics are typical of current production.  
Whilst future production will conform to specification, variations may occur.

## ➤ FLUID FORCE 2000 HOUR – SCREW UNIVERSAL LUBRICANT

A high quality compressor lubricant developed for lubrication of oil injected Screw Compressors. A hard working, reliable lubricant to deliver robust protection and lubrication at a competitive price.

Available in 5, 20 & 209 Litre packs with BLACK identifying cap.



CompAir policy is one of continuous improvement and we therefore reserve the right to alter specifications and prices without prior notice. All products are sold subject to the Company's conditions of sale.



J. Applesseed